



HIGH BAY THOR HOT

Certifikáty



Charakteristika

označení	příkon	účinnost	světelný tok	CTT	CRI	teplota	rozměry
ST-KC-T2	60 W	135 lm/W	8100 lm	4000 K	Ra 80,Ra 90	-30°C - +70°C	420x260x76 mm
ST-KC-T2	80 W	135 lm/W	10800 lm	4000 K	Ra 80,Ra 90	-30°C - +70°C	420x260x76 mm
ST-KC-T2	100 W	135 lm/W	13500 lm	4000 K	Ra 80,Ra 90	-30°C - +70°C	420x260x76 mm
ST-KC-T2	120 W	135 lm/W	16200 lm	4000 K	Ra 80,Ra 90	-30°C - +70°C	420x260x76 mm
ST-KC-T3	150 W	135 lm/W	20250 lm	4000 K	Ra 80,Ra 90	-30°C - +70°C	520x290x85 mm
ST-KC-T3	180 W	135 lm/W	24300 lm	4000 K	Ra 80,Ra 90	-30°C - +70°C	520x290x85 mm
ST-KC-T3	210 W	135 lm/W	28350 lm	4000 K	Ra 80,Ra 90	-30°C - +70°C	520x290x85 mm
ST-KC-T3	230 W	135 lm/W	31050 lm	4000 K	Ra 80,Ra 90	-30°C - +70°C	520x290x85 mm

Vlastnosti produktu

